

D892M



Wi-Fi

Wireless
Handset

Bluetooth



USB port

Anti-bacterial
housingExpansion
module
connectable

HD audio



SmartLabel

Security (TLS
& SRTP)

OpenVPN

Premium IP Desk Phone with integrated Wireless Mobility

The Snom D892M builds on the D8xx legacy as a true all-rounder, now with a built-in Wireless receiver for up to 50 m wireless mobility and a cleaner desk. Ten SmartLabel keys with LED backlighting offer flexible customisation. Its 40° adjustable LCD ensures vibrant colours and readability in any light. With integrated

Bluetooth, Wi-Fi, and hearing aid compatibility, the D892M is a connectivity powerhouse. Designed for professionals handling high call volumes and complex IT environments, it's a future-ready desk phone combining usability with cutting-edge wireless tech.

Basics

- Product information
 - IP desk phone | Wireless handset D8M | gunmetal black | PN 00004539
 - Contactless charging
 - Operating system: Linux
 - Anti-bacterial housing
- Placement
 - Indoor, desktop, wall mounting¹

Dimensions and weight

- Dimensions (L × W × H, approx.)
 - 210 mm × 243 mm × 45 mm without footstand
 - 193 mm × 243 mm × 165 mm with footstand
- Weight (approx.)
 - 1.12 kg with footstand

Display and indicators

- Display
 - TFT liquid crystal display (LCD): tiltable, IPS panel, true colour, backlit
 - Size (diagonal): 5.0" (127 mm)
 - Size (W × H): 110 mm × 62 mm
 - Resolution: 1,280 × 720 pixels
- IP desk phone: 15 LED indicators
 - Call status indication: 1 red LED
 - Message waiting indication (MWI): 1 red LED
 - Function key status indication: 10 multicolour LEDs
 - Audio key status indication: 3 LEDs (1 red / 2 green)
- Wireless handset: 1 LED indicator
 - Charging indication: 1 multicolour LED

Keypad and function keys

- IP desk phone: 43 hard keys in total
 - 12 keys (standard ITU telephone keypad)
 - 5-way navigation key
 - 4 context-sensitive function keys
 - Programmable function keys:
 - 10 SmartLabel keys (with multicolour LED)
 - Key mapping of up to 40 functions (10 keys × 4 pages)
 - 5 dedicated audio keys
 - Mute (with red LED)
 - Speakerphone (with green LED)
 - Headset (with green LED)
 - Volume + / -
 - 7 dedicated function keys
 - Cancel
 - Message (with red LED)
 - Directory
 - Transfer
 - Hold
 - Conference
 - Redial
- Wireless handset: 5 hard keys in total
 - 3 dedicated audio keys
 - Volume + / -
 - Mute / Unmute
 - 2 dedicated function keys
 - Onhook / offhook
 - Power on / off
- Related features
 - Keyboard lock
 - Expansion module connection via USB port for up to 3 × D8C¹

Audio devices, codecs and features

- IP desk phone: Casing microphone | Casing speaker
 - 2 dedicated microphones
 - Frequency range: 100 Hz - 14.0 kHz
 - Speakerphone mode: Full duplex, HD audio
- Wireless handset: Microphone | Handset earpiece
 - Noise cancellation, HD audio
 - Frequency range: 150 Hz - 8.0 kHz
 - Hearing aid compatible (HAC)
- Audio codecs: G.711 (A-law, μ -law), G.722, G.723.1, G.726, G.729, Opus
- Dual-tone multi-frequency signalling (DTMF / RFC2833): SIP-INFO, in-band, out-of-band
- Related features
 - Comfort Noise Generator (CNG)
 - Voice Activity Detection (VAD)
 - Audio response time
 - Adaptive jitter buffer
 - Packet loss concealment (PLC)

Interfaces and connections

- Power options: IP desk phone
 - [Power over Ethernet \(PoE\)](#): IEEE 802.3af, class 3 | IEEE 802.3az³
 - Power adapter:¹ 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 3 A, 15 W
- Power options: Wireless handset
 - Battery: 850 mAh, lithium-ion, non-removable, rechargeable, up to 12 h wideband talk time, up to 200 h standby time, up to 8 h charging time
- Wired interfaces
 - Power adapter: coaxial power connector (socket)
 - Network connectivity: 2 × RJ45-8P8C sockets (NET / PC) → Gigabit Ethernet (GbE)
 - USB connectivity: 2 × USB 2.0 type A ports
 - Corded handset:¹ RJ9-4P4C socket
 - Headset:¹ RJ9-4P4C socket

- [EHS adapter](#):¹ RJ12-6P6C socket
- Wireless interfaces
 - Wireless handset
 - Network connectivity: Wireless LAN
 - [Headset connectivity](#): Bluetooth
- Sensors
 - Hook switch sensor

User interfaces and setup

- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
 - Visual and functional UX based re-design (phone manager)
 - Password-protected login
 - Secure web server/client (HTTPS)
- [Configuration and setup via menu-driven phone user interface \(PUI\)](#)
- [Automatic configuration via provisioning](#)
 - Loading of settings and firmware via HTTP, HTTPS, TFTP
 - Supported DHCP provisioning options 43 / 60 / 66 / 67
 - [Secure Redirection And Provisioning Service \(SRAPS\)](#) support
 - [Remote management via TR-069 / TR-069 Annex G \(TR-111\) / TR-369](#)
 - Plug & Play (PnP) support
- Localization
 - [Languages](#)
 - Time zone, dial tone
- Diagnostic
 - SIP / PCAP trace
 - Syslog
- Related features
 - Local call recording via USB
 - Dual firmware partition

Networking technologies and protocols

- Wireless LAN
 - Frequency band (2G): 2,400.0 - 2,483.5 MHz
 - IEEE 802.11b (Wi-Fi 2): up to 11 Mbps
 - IEEE 802.11g (Wi-Fi 3): up to 54 Mbps
 - IEEE 802.11n (Wi-Fi 4): up to 150 Mbps
 - Frequency band (5G): 5,150 - 5,350 MHz and 5,470 - 5,725 MHz
 - IEEE 802.11a (Wi-Fi 1): up to 54 Mbps
 - IEEE 802.11n (Wi-Fi 4) up to 150 Mbps
 - IEEE 802.11ac (Wi-Fi 5) up to 433 Mbps
- Network technologies
 - [OpenVPN](#), [VLAN \(IEEE 802.1q\)](#)
 - Bluetooth: BT 5.0, class 2
- VoIP related protocols and techniques
 - [SIP](#), [SDP](#), [RTP](#), [RTCP](#), RTCP-XR, SIP REFER method (RFC 3515), rport (RFC 3581), [ENUM](#), ICE, [STUN](#)
- Secure VoIP protocols
 - [SIPS \(SIP over TLS\)](#), [SRTP](#), [SRTCP](#)
- Network protocols
 - IPv4 / IPv6 (dual stack), [DHCP](#), NTP, [LDAP](#), [LLDP-MED](#), HTTP, [TFTP](#), [L2TP](#)
- Secure network protocols
 - [TLS V1.3](#) incl. ciphers (forward secret & authenticated), HTTPS, [IEEE 802.1X \(EAP-TLS - RFC 5216\)](#)
- Remote management protocols
 - [TR-069](#), TR-069 Annex G (formerly TR-111), [TR-369 \(USP\)](#)

Directory support and call features

- 12 SIP identities / accounts
 - Up to 12 simultaneous calls
- Directory support
 - [LDAP \(server-based directory\)](#)

- [Local directory with up to 50,000 entries](#)
- Import/export phone book (CSV, XML)
- [XML phonebook support](#)
- Outgoing call features
 - Speed dialling via function keys
 - Speed dialling
 - [URL dialling](#)
 - [Local dial plan](#)
 - Redial (via dialed calls list)
 - Automatic redial on busy
 - Caller identification (CLIP)
 - Calling Line Identification Restriction (CLIR)
 - [Call completion \(busy/unreachable\)²](#)
 - [Intercom](#)
 - [Multicast paging](#)
- Incoming call features
 - [Call waiting/swapping](#)
 - Auto answer
 - [Call diversion](#)
 - **[Call barring / blocking](#)**: deny list, [dynamic central blacklist check²](#), anonymous calls, Do Not Disturb (DND) mode
- Connected call features
 - Mute microphone
 - Hold
 - Music on hold²
 - [Blind call transfer](#)
 - [Attended call transfer](#)
 - 5-way (4+1) local conferencing
 - Call park / unpark²
 - Client Matter Code (CMC)²
- Related features
 - Call history lists of missed, received, dialed, rejected, and deflected calls
 - [Extension monitoring \(Busy lamp field\)](#), [call pickup²](#)

Package contents

- Hardware
 - IP desk phone D892M
 - Wireless handset : D8M (PN 00004557)
 - Metal pin (to switch power on/off)
 - Footstand
 - Ethernet cable: 1.5 m
- Documentation
 - **Safety instructions**

Interoperability

- **Certified VoIP partner**

Environmental conditions

- Operating ambient temperature:
 - 0 °C - +35 °C
- Nonoperating (storage) temperature:
 - -10 °C - +45 °C
- Humidity (non-condensing):
 - 5 % - 95 %

Snom accessories and compatible devices

- Power adapter
 - Snom 15W PSU (PN 00004715)
- PoE injector
 - **A5E (PN 00004679)**
- Expansion module
 - **D8C (PN 00004562)**
- Wall mount kit
 - D8xx WM (PN 00004544)
- Wireless handset
 - **D8M (PN 00004557)**
- Corded wideband handset
 - D8xx-WB-HS (PN 00004561)
- **EHS adapter**
 - **EHS Advanced 2.0 (PN 00002362)**
- Wired headset via RJ9
 - Binaural: **A310D (PN 00004626)**
 - Monaural: **A100M (PN 00004341)**, **A310M (PN 00004624)**
- Wired headset via USB
 - Binaural: **A330D (PN 00004598)**
 - Monaural: **A330M (PN 00004597)**
- BT headset via integrated Bluetooth
 - **A350M (PN 00004658)**
- Wireless headset via USB / RJ9+EHS
 - **A170C (PN 00004733)**
- Wireless conference speakerphone (USB)
 - **C300 (PN 00004584)**

Snom accessories and compatible devices



15W PSU



A5E



D8M



D8C



EHS 2.0



C300



A100M



A170C



A310M



A310D



A330M



A330D



A350M

¹ Available separately

³ Optional via software

² If supported by PBX

Series overview



D810W



D812



D815W/ WB



D862



D865



D892M



D8C

Disclaimer

Further information: [Snom D892M webpage](#) | [Snom Service Hub D892M](#) | [Safety instructions D892M](#) | [Short User Manual D892M](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.